Louis Savinien Dupuis Journal of Multidisciplinary Research, 2025: V(4) 54–58
DOI: 10.21839/lsdjmr.2025.v4.243

Research Article

Applications of Graph Coloring

Aruna S*
Department of Mathematics,Immaculate college for womens cuddalore, India

(Received: 09-04-2025; Accepted 08-06-2025; Published Online 03-11-2025)

Abstract

Graph coloring represents a foundational pillar of graph theory, centered on the strategic assignment of labels to graph components under specific restrictive rules. The most common iteration, vertex coloring, involves utilizing a set of K colors to ensure that no two connected vertices share the same identity; these principles similarly extend to the coloring of edges and faces. Beyond its theoretical roots, this concept serves as a critical problem-solving framework in modern computer science, facilitating advancements in data mining, networking, Sudoku puzzles, and the analysis of bipartite graphs. By providing a mathematical structure for conflict resolution, graph coloring is instrumental in diverse logistical fields. This paper specifically explores its practical utility in optimizing final exam timetabling, managing aircraft scheduling, and solving the spatial complexities of guarding an art gallery

Keywords: Graph, vertex. Edge, Colouring

Introduction

Graph coloring is one of the most important and widely studied topics in graph theory, a branch of discrete mathematics. It deals with the assignment of colors to certain elements of a graph, such as its vertices, edges, or regions, under specific constraints. The main objective of graph coloring is to ensure that no two adjacent or related elements share the same color. This concept may seem simple at first, but it as deep mathematical significance and numerous real-world applications. A graph consists of a set of vertices (ornodes) connected by edges. In many practical situations, these vertices represent objects, and the edges represent relationships or conflicts between them .Graph coloring provides a systematic way tohandlesuchconflictsbyassigningdifferentcolorstoconflictingelements.Theterm “color” is used in an abstract sense; it can represent frequencies, time slots, labels, or any distinct identifiers depending on the context.

TheoriginofgraphcoloringdatesbacktothefamousFourColor Theorem,which waspropose dinthe19thcentury.Thistheoremstatesthatanyplanarmapcanbecolored usingatmostfourcolorssuchthatnotwoadjacentregionssharethesamecolor.This problemwasoneoftheearliest andmostwell-knownproblemsingraphtheory and tookover a century to be proven. It laid the foundation for the development of graph coloring as a mathematical discipline and inspired many researchers to explore its properties andapplications. Graph coloring is generally categorized into several types, including vertexcoloring,edgecoloring,andfacecoloring. Amongthese,vertexcoloringisthemost commonlystudied.Invertexcoloring,colorsareassignedtoverticesinsuchawaythatno two adjacent vertices (vertices connected by an edge) have the same color.

The minimum number of colors required to achieve such a coloring is known as the chromatic number of the graph. Determining the chromatic number of a graph is one of the central problems in graph theory and is often computationally challenging. Another important type is edge coloring, where colors are assigned to edges so that no two edges sharing a common vertex have the same color. Similarly, face coloring applies to planar graphs, where regions formed by edges are colored under certainconditions.Each type of coloring has itsown rules and applications, making graph coloring a rich and diverse area ofstudy.

Graph coloring is not just a theoretical concept; it has numerous practical applicationsinvariousfields.Forexample,inschedulingproblems,tasksthatcannotoccur simultaneously are represented as adjacent vertices in a graph. By coloring the graph, one can assigntimeslotstotaskswithoutconflicts.Similarly,infrequencyassignmentproblems, radio frequencies must be assigned in such a way that interfering transmitters do not use the samefrequency.Graphcoloringprovidesanefficientwaytosolvesuchproblems.In computer science, graph coloring is used in register allocation, where variables in a programare assigned to a limited number of CPU registers. It is also applied in solving

puzzles like Sudoku,wherenumbersmustbeplacedwithoutviolatingconstraints. Innetworking,ithelps inchannelassignmentandavoidinginterference.Theseexampleshighlighttheversatility andimportanceofgraphcoloringinsolvingreal-worldproblems.Thestudyofgraph coloringalsoinvolvesvariousalgorithmsandtechniques.Someofthesealgorithmsare simple and easy to implement, while others are more complex and designed to handle large graphs efficiently.Despite its simplicity, graph coloring is known to be an NP-hard problem in general, meaning that there is no known efficient algorithm to solve all cases quickly. This makes it an active area of research in both mathematics and computer science. In addition to its practical applications, graph coloring also has significant theoretical importance. It helps inunderstanding the structure and properties of graphs, such as connectivity, planarity,andcycles. It also leads to the development of new mathematical concepts and theorems. Researchers continue to explore new variations and extensions of graph coloring, such as list coloring, total coloring, and fractional coloring. Graph coloring is a fundamental concept in graphtheory withboththeoretical andpractical significance.It provides apowerful frameworkforsolvingproblemsinvolvingconflictsandconstraints. Fromitshistoricalroots inthe Four Color Theorem to itsmodern applications in technology andscience,graph coloring remains an essential and dynamic area of study. Its ability to model real-world problems and provide efficient solutions makes it a valuable tool in various disciplines.Alon, N. (1993) explained Restricted colorings of graphs.Alon, N., & Tarsi, M. (1992) elucidated Colorings and orientations of graphs. Combinatorica, Andren,L.J. described AvoidabilitybyLatinsquaresofarrayswithevenside.Appel, K., & Haken, W. (1977) researched Every planar map is four colorable. Appel, K., Haken, W., & Koch, J. (1977) explained Every planar map is four colorable. Asratian, A. S., &Casselgren, C. J. (2006) investigated Some results on interval edge colorings of (a,)-biregular bipartite graphs. Asratian, A. S., et al. (1998). Bipartite graphs and their applications. Cambridge University Press, Cambridge.Asratian, A. S., &Kamalian, R. R. (1987) looked over Interval coloring of the edges of a multigraph.Asratian, A. S., &Kamalian, R. R. (1994) probed Investigation on interval edge-colorings of graphs. Axenovich, M. A. (2002) exploredOn interval colorings of planar graphs. Biggs, N. L., Lloyd, E. K., & Wilson, R. J. (1976)scrutnized*Graph theory*

APPLICATIONSOF GRAPHCOLOURING

AIRCRAFTSCHEDULING

Managing afleetofkaircraftfornscheduledflightsrequires aconflict-free assignment strategy. Each flight is defined by a specific time interval, and if two flights have overlapping schedules, they cannot be assigned to the same aircraft. To solve this, a "clash graph" is constructed where each vertex represents a flight and edges connect flights with overlapping time windows. Because this resulting graph is an interval graph, it can be colored optimally using polynomial-time algorithms, allowing planners to determine the minimum number of planes needed to cover all flights.

BI-PROCESSORTASKS

In high-performance computing, certain complex tasks must be executed by twospecific processors working in tandem at the same time. Since a single processor can only handleonetaskatatime,schedulingthesebi-processor jobsismodeledusing edgecoloring. Inthisgraphmodel,processorsarerepresentedbyvertices,andeachtaskrequiring processors i and j is represented by an edge connecting them. The goal is to assign "colors" (timeslots)totheseedgessothatnotwoedgesincidenttothesameverte xshareacolor. While this problem is generally NP-hard, Vizing's Theorem provides an efficient solution for simple graphs, guaranteeing that the tasks can be completed using no more than (Δ + 1) time slots, whereΔ is the maximum number oftasks assigned to any one processor.




Figure3.1Multipleedgegraph

FREQUENCYASSIGNMENT

In the field of telecommunications, Frequency Assignment is modeled as a graph coloring problem toprevent signal interference betweenneighboring radio stations.Stations are represented as vertices on a plane, and those within close proximity where their signals might overlap are connected by

edges in a "conflict graph". While one might assume the Four ColorTheoremapplies,real-worldclustersofstationsoftenformcomplexnetworksknown asunitdiskgraphs,whereverticesareconnectediftheircorrespondingcircularcoverage areas intersect.

Becausedenseclusterscanformlargecliques(wheremany stationsinterferewith each other simultaneously), simple planar coloring is often insufficient. Instead, researchers utilize specialized algorithms, such as 3-approximation algorithms for coloring unit circle graphs, to efficiently assign frequencies and minimize the spectrum used while ensuring clear communication for all base stations in the network.


GuardinganArtGallery

The Art Gallery Theorem is a fundamental problem in computational geometry that determines the minimum number of observers required to monitor the interior of a polygonal floor plan. To solve this, a simple polygon with n vertices is first triangulated, dividing the space into non-overlapping triangles.By applying a 3-coloring algorithmtothe resulting graph, every vertex is assigned one of three colors such that no two connected vertices sharethe same color. Since every individualtriangle must contain all three colors, placing a cameraat every vertex of a single color class ensures that everypointwithinthepolygonisvisible to at least one observer.

Mathematically,Chavatal'sWatchmanTheoremprovesthat⌊n/3⌋camerasare always sufficient, and occasionally necessary, for full coverage. To optimize security costsand monitoring efficiency, we select the smallest color class (the color appearing least frequently).As shown in theprovided example,withvertex counts of6,7, and6, choosing the black or green color classes allows for complete surveillance using the minimum numberof cameras required.

Figure3.2Camerasareusedforguardinganartgallery.

To analyze the art gallery problem with geometric precision, we first represent the exhibition floorplan as asimplepolygonina2Dplaneregionenclosedby asingle,non- self-intersecting polygonal chain without holes. Within this model, a camera's position corresponds to a specific point in the polygon. A camera "sees" or monitors any point withintheinteriorifthelinesegmentconnectingthetwoliesentirelywithinthepolygon's boundaries. By applying triangulation, we can



decompose the complex shape into non- overlapping triangles.Using a3-coloring algorithmontheverticesofthesetriangles,we ensurethat every trianglecontainsallthreecolors.By placing camerasatthevertices belonging to the smallest color class, we guarantee complete surveillance of the interior. Chavatal's Watchman Theorem proves that for a polygon with n vertices, ⌊n/3⌋cameras are always sufficient

Figure3.3Asimplepolygon





Figure3.4APossibleTriangulationofthePolygon

Onceasimplepolygonhasbeentriangulated,itbecomes agraphthat canbe3- colored. This means each vertex is assigned one of three colors such that every individual triangle within the polygon contains all three. This property is the foundation for the ArtGallery Theorem,which statesthat any polygonwith nvertices can befully monitored using no more that [n/3] cameras. While placing a camera at a single vertex often provides visibility beyond the immediate adjacent triangles, there are specific "comb-shaped" polygons where[n/3] cameras are strictly necessary. Therefore, this formula represents the "worst-case" requirement that is always sufficient to ensure every interior point is visible to at least one observer.






Figure 3.5 3-Coloring of the Triangulated Polygon, take the smallest color class to place the cameras. Here, we can choose black or green color class to place the cameras.

COMPUTATIONALSTRATEGYFORARTGALLERYGUARDING

While Chavatal's Watchman Theorem guarantees that [n/3] cameras are always sufficient to monitor a simple polygon with n vertices, identifying the optimal placement requires an efficient algorithmic approach. The process begins by triangulating the polygonal floor plan a task that can be accomplished in O(n log n) time. To facilitate rapid navigation betweenadjacenttriangles,thetriangulationistypicallystoredinadoubly-connectededge list (DCEL), allowing for constant-time transitions to neighboring faces.

Once the representation is established, we apply a 3-coloring algorithm to the vertices. This is achieved by performing a Depth-First Search (DFS) on the dual graph of the triangulation, where each triangle represents a node. Because the dual graph of a triangulated simple polygon is always a tree, we can consistently assign one of three colors to each vertex such that every triangle contains all three.

Finally, to minimize the security footprint and hardware costs, we select the smallest color class the set of vertices appearing least frequently as our camera locations. As demonstrated in the example where color counts are 6, 7, and 6, selecting either the black or green color class ensures fullsurveillance with the minimum possible number of devices.

OPTIMIZATION AND THE ART GALLERY THEOREM

TheArtGalleryTheoremprovidesamathematicalguaranteefortheminimum number of observers required to monitor a polygonal space. Once a simple polygon with n vertices has been triangulated, it is always possible to perform a 3-coloring of the vertices. In this coloring scheme,every individual triangle is guaranteed to have all three colorsrepresented at its corners. By placing a camera at every vertex belonging to the smallest color class, we ensure that every triangle and thus the entire polygon is fully monitored. While a single camera often monitors more than just its adjacent triangles, Chavatal's Watchman Theorem proves that [n/3] cameras are always sufficient, and in some worst-case "comb" polygons, strictly necessary. As shown in the figure, comparing the color classes (Black: 6,Red: 7, Green: 6) allows us to choose either the black or green set to achieve complete surveillance with the minimum number of devices.

FINAL EXAMTIME TABLING AS A GROUPING PROBLEM

The challenge of scheduling university final exams can be modeled as a complex grouping problem that often reduces to a graph coloring issue. In this context, Linear Linkage Encoding(LLE)hasemergedas aneffectiverepresentationfor evolutionary algorithmsused in data clustering and timetabling. The goal is to assign exam periods (time slots) to a set of subjects while satisfying various constraints, such as ensuring no student is scheduled for two exams simultaneously.

To solve this, researchers have applied several computational strategies, including Genetic Algorithms (GA), multi-objective evolutionary algorithms focused on Pareto positioning, and Memetic Algorithms (MA). These methods aim to minimize both intra- group and inter-group conflicts. By treating each exam as a vertex and each conflict (shared students) as an edge, the scheduling task becomes a matter of finding the chromatic numberof the graph—the minimum number of time slots required to ensure a conflict-free examination period.

CONCLUSION

In summary, graph coloring transcends its origins as a theoretical mathematical exercise to serve as a vital computational tool for modern resource management. By transforming complex constraints into a structured framework of vertices and edges, it becomes possible to resolve logistical conflicts that would otherwise be computationally overwhelming. Whether it is preventing scheduling overlaps in university examinations, streamlining the intricate rotations of aircraft, or optimizing the placement of security personnel in an art gallery, graph coloring provides a precise and scalable methodology for efficiency. As computer science continues to evolve, the principles of vertex, edge, and face coloring remain essential for navigating the increasing complexities of data organization and spatial logistics.

REFERENCES

1. Alon, N. (1993). Restricted colorings of graphs. *Surveys in Combinatorics, Proc. 14th*British Combinatorial Conference, Cambridge University Press, 1-33.
2. Alon, N., & Tarsi, M. (1992). Colorings and orientations of graphs. Combinatorica, 12, 125-134.

3. Andren,L.J.AvoidabilitybyLatinsquaresofarrayswithevenside(submitted).
4. Appel, K., & Haken, W. (1977). Every planar map is four colorable. I. Discharging. Illinois J. Math., 21, 429-490
5. Appel, K., Haken, W., & Koch, J. (1977). Every planar map is four colorable. II. Reducibility. Illinois J. Math., 21, 491-567.
6. Asratian, A. S., &Casselgren, C. J. (2006). Some results on interval edge colorings of (a,)-biregular bipartite graphs. Research report LITH-MAT-R-2006-*09*, Linköping University.
7. Asratian, A. S., et al. (1998). Bipartite graphs and their applications. Cambridge University Press, Cambridge.
8. Asratian, A. S., &Kamalian, R. R. (1987). Interval coloring of the edges of a multigraph (in Russian). Applied Math., 5, 25-34.
9. Asratian, A. S., &Kamalian, R. R. (1994). Investigation on interval edge-colorings of graphs. *J. Combin. Theory Ser. B*, 62, 34-43.
10. Axenovich, M. A. (2002). On interval colorings of planar graphs. Congr. Numer., 159, 77-94.